

Disabled Toilet Alarm DT7520.21

Beacon Call Point Vertical Stainless

DT 7800-112 DS1 V1.02 28/07/2014 Disabled Toilet Alarm Beacon Call Point Vertical Stainless



BEACON CALL POINT

Combined beacon call point function

Stainless steel fascia

Vandal resistant call button

Large high intensity 20 mm LED beacon

Activation delay

Anti-tamper fixings

Flush or surface mount in 35 mm double gang back box

Compatible with remote monitoring systems

IP/serial/digital BMS interfaces available

CUSTOMISED PANELS AVAILABLE ON REQUEST

FOR DISABLED TOILET ALARMS

FOLKNOLL DISABLED TOILET ALARM SYSTEMS

Our disabled toilet alarm series is a range of flexible, easy to install and operate equipment, enabling you to install cost effective vandal resistant disabled toilet alarm systems. Using this range you can construct anything from stand-alone toilet alarms to site-wide systems with remote fault monitoring, events logs, graphical workstations etc.

DT7520.21 BEACON CALL POINT

Our DT520.21 Beacon Call Point combines the functions of alarm beacon and emergency call point into a single vandal resistant stainless steel unit.

These units are usually mounted on the wall inside a toilet to enable users to call for assistance.

The beacon is illuminated when the alarm is activated to provide reassurance that the alarm has been activated.

The call button must be held for at least 0.25 seconds to reduce the risk of accidental alarm calls.

The standard unit is annotated in black with the word **CALL**; alternative annotation is available on request.

These beacon call point can be mounted in double gang 35 mm flush or surface back boxes (not supplied).



Disabled Toilet Alarm DT7520.21

Beacon Call Point Vertical Stainless

DT 7800-112 DS1 V1.02 28/07/2014 Disabled Toilet Alarm Beacon Call Point Vertical Stainless

PART NUMBERS

DT7520.21 Beacon call point, vertical stainless steel

SPECIFICATIONS

Fascia: Brush finished stainless steel

Mounting: Surface or flush mount in 35 mm double gang back

box(not supplied).

Dimensions: Width: 86 mm, height: 86 mm, depth: < 35 mm (approx.)

Power: Line powered

DESIGNED FOR LIFE

At Folknoll all equipment is designed by experienced engineers for easy installation, simple configuration, straightforward operation, low maintenance and high reliability.

CUSTOM UNITS

Folknoll is a customer focused company. If you need special software features, custom made units or special systems please contact Folknoll and discuss your requirements with one of our engineers.

FURTHER INFORMATION

For further information or support for any of our wide range of products, systems and services please contact **Sales** at **Folknoll**, **Old North Rd**, **Royston**, **HERTS**, **SG8 5DT**, **UK**.

Tel: +44 (0) 1763 234567 Email: sales@folknoll.co.uk www: www.folknoll.co.uk