

Folknoll DT 7800-139 SPECIFICATIONS

ALARM STRIP SYSTEMS

ALUMINIUM BASE	Alloy	6063T6
	Finish	Bright Anodised AA5
		Satin Silver Anodised AA5

DIMENSIONS	Width	60mm
	Depth	14mm
	Length	2000mm (standard base)
	Weight	0.665 kg/mt

ACTIVATION INSERT	Materials	Flexible PVC-DVF406
	Dimensions (external)	Standard rolls - 5, 10, 15m
	Max width	54mm
	Max depth	9mm
	Active impact zone	34mm
	Weight (inc Copper)	0.353kg/m
	Colours	Red- 033HMF/25K-200 Green - GN590HMF/25K-200 Blue -BE047HMF/25K-200
	Elongation @ break	380%
	Shore A15 hardness	63
	UV stabilised	Yes
	Cold flex temperature	-28C
	Tensile	14Mpa
	I.P. rating	IP65

CONTACT CONDUCTOR	Material	ED Copper
	Width	10mm
	Quality	CTS790
	Treatments	Zinc-Chromate Passivated

LED LIGHT STRIP	Dimensions	8mm x 2.5mm
	No of LEDs	30/m
	Colour	Bright White
	Operating temperature	-25C to +60C
	Voltage	12Vdc
	LED life	50,000 hours
	Power consumption	180mA/metre@12Vdc

LED CONTROLLER	Supply voltage	12 Vdc
	Supply current	80mA + LED current

END CAPS	Construction	2 part - self locking
	Material	ABS
	Weight	42g (set)

ABOUT FOLKNOLL

We are a UK based systems design, manufacturing and installation company. Since 1975 we have been supplying tough, reliable, practical, alarm and control systems for the private and public sectors. All of our products and systems have been designed for easy installation and low maintenance by experienced engineers. As original manufacturers, all of our products and systems can be customised to suit your requirements. We also offer individual annotation, custom engraving and special finishes for all of our equipment.

GET IN TOUCH

Please contact us for further information about our wide range of products and services and find out how we can provide a solution for you.



Folknoll Group Ltd

Old North Rd, Royston, HERTS, SG8 5DT, UK

www.folknoll.co.uk

+44 (0) 1763 234567

enquiries@folknoll.co.uk