



VANDAL-RESISTANT, ILLUMINATED RESET BUTTON WITH SOUNDER

Large, illuminated, push button

Integral sounder

Can be 'daisy-chained' for multiple reset points

Tough, stainless steel, construction

Mounts in a standard UK, 35mm, single gang, back box,
anti-tamper fixings available

Compatible with Folknoll emergency assistance alarms

IDEAL FOR NIOSP SYSTEMS

EMERGENCY ASSISTANCE ALARMS

Folknoll emergency assistance alarm systems offer cost-effective, vandal resistant, **BS 8300-2** and **DOCUMENT M** compatible solutions built from standard and bespoke units. Our alarms can be combined with disabled refuge EVCS and other systems. Ideal for **SHOPS, OFFICES, HOTELS** and other **PUBLIC SPACES**.

EMERGENCY ASSISTANCE RESET POINTS

Reset points reset/cancel the local alarm. **BS 8300-2** compliant emergency assistance alarms cannot be reset remotely. To comply these standards - and to try and ensure alarm responders visit the location in response to an alarm - one or more reset points are usually installed inside each alarm zone.

DT7540.00P RESET, BUTTON, ILLUMINATED, SOUNDER

A vandal resistant, illuminated reset button with an integral sounder for Folknoll alarm systems. These units can be linked together to offer multiple reset points and be used as a reset button for an alarm controller or an additional reset point for an enhanced reset.

ACTIVATION DELAY

When used in conjunction with Folknoll emergency assistance alarms, this button must be held for a minimum of 0.25 seconds before it will operate. Reducing the risk of accidental operation.

BUTTON ILLUMINATION AND SOUNDER

The button illumination and sounder are usually wired to mimic the action of the over-door beacon sounder. Reassuring the users by giving the user positive audio and visual alarm state indication within the alarm zone. Other configurations available on request.

FACEPLATE

The standard faceplate is made from brushed finish stainless steel with bold back, silk screened, English legends. Other finishes and alternative annotation are available on request.


MOUNTING

The unit is designed for mounting in a standard >35mm, single gang, UK back box. Anti-tamper fixings are available on request.

SPECIFICATIONS

Faceplate:	Brushed finish stainless steel (other finishes available on request)
Annotation:	Bold black silk screen as standard (other options available on request)
Button:	Large vandal resistant, momentary, push button
Alarm state indicator:	Red LED button illumination (other colours available on request)
Mounting:	Standard UK, 35mm, single gang, back box (not supplied)
Dimensions:	Width: 86mm, height: 86mm, depth: <35mm (approx.)
Power:	12Vdc / 24Vdc

EXAMPLE FACEPLATES



ABOUT FOLKNOLL

We are a UK based systems design, manufacturing and installation company. Since 1975 we have been supplying tough, reliable, practical, alarm and control systems for the private and public sectors. All of our products and systems have been designed for easy installation and low maintenance by experienced engineers. As original manufacturers, all of our products and systems can be customised to suit your requirements. We also offer individual annotation, custom engraving and special finishes for all of our equipment.

GET IN TOUCH

Please contact us for further information about our wide range of products and services and find out how we can provide a solution for you.



Folknoll Group Ltd

19 Old North Rd, Royston, HERTS, SG8 5DT, UK

www.folknoll.co.uk

+44 (0) 1763 234567

enquiries@folknoll.co.uk